



PART NUMBER 40A-52A-XXY-78A-11
 ITEM NAME MULTI-WAVELENGTH LASER

PRODUCT DATASHEET



DESCRIPTION

Uncover new possibilities in your research with our state-of-the-art 3-Wavelength Laser Combiner—a compact powerhouse designed to revolutionize life sciences and fluorescence applications. Seamlessly integrating four distinct wavelengths into a single housing, this device offers unparalleled convenience without compromising on performance.

Features:

- Three wavelengths
- Plug-and-play
- Single user interface for all 3 wavelengths

Advantages:


- Space-saving design
- No optics realignment
- Remote PC control

SPECIFICATIONS

Specifications updated: 14 March 2024

Parameter	Minimum Value	Typical Value	Maximum Value
Output power, mW	-	405 nm - 120 520 nm - 80 785 nm - 120 ¹	-
Wavelength tolerance, nm	400 515 782	405 520 785	410 530 788
Longitudinal modes	-	Multiple	-
Spectral line width FWHM, nm	-	1	2
Power stability, % (RMS, 8 hrs)	-	0.2 ²	1
Intensity noise, % (RMS, 20 Hz to 20 MHz)	-	0.5 ³	1
Transversal modes	-	TEM00	-
Polarization direction	-	Horizontal	-
Polarization contrast	405 nm - 50 520 nm - 10 785 nm - 10	405 nm - 300 520 nm - 50 785 nm - 50	-
Control interface type	-	UART ⁴	-
Operation mode	-	ACC (CW)	-
Input voltage, VDC	8	9	12
External power supply requirement	-	+9 V DC, 1.5 A ⁵	+12 V DC, 1.5 A
Dimensions (WxDxH), mm	-	50 x 30 x 18 ⁶	-
Beam height from the base, mm	-	10.4	-
Heat-sinking requirement, °C/W	-	<0.5	-
Optimum heatsink temperature, °C	-	25	-

TYPICAL NEAR FIELD




Warm up time, mins (cold start)	-	< 1	2
Temperature stabilization	-	Internal TEC	-
Overheat protection	-	Yes	-
Storage temperature, °C (non-condensing)	-	-	-
Net weight, kg	-	0.3	-
Power consumption, W	-	2 ⁷	18
Warranty, months (op. hrs)	-	14 (10000) ⁸	-
RoHS	-	Yes	-
CE compliance	-	- General Product Safety Directive (GPSD) 2001/95/EC - (EMC) Directive 2004/108/EC	-
OEM lasers are not compliant with	-	IEC60825-1:2014 (compliant using additional accessories)	-
Modulation bandwidth, MHz	-	10 ⁹	-

- ¹ The optical power can be tuned from virtually 0% to 100% by changing the driving current of the laser diodes. However, other specifications, such as central wavelength, power stability, noise, polarization ratio, beam shape, quality, and circularity are not guaranteed at power levels other than factory preset power. Significantly worse power stability is to be expected at very low power levels, e.g. <3% from specified nominal power.
- ² The long term power test is carried out at constant laser body temperature (+/-0.1 °C) using an optical power meter with an input bandwidth of 10 Hz. The actual measurement rate has a period of about 20 seconds to 1 minute.
- ³ Noise level is measured with a fast photodiode connected to an oscilloscope. The overall system bandwidth is from 2 kHz to 20 MHz.
- ⁴ Break-out-boxes AM-C8 and AM-C3 can be used for conversion of UART communication to either USB or RS232.
- ⁵ If the break-out-box AM-C9 is used, a PD (Power Delivery) type of power supply can be used.
- ⁶ Excluding control interface pins and an output window/fiber assembly.
- ⁷ For single enabled wavelength.
- ⁸ Whichever occurs first.
- ⁹ TTL digital modulation up to 10 MHz.

Note: Product specifications are subject to change without prior notice to improve reliability, function or design or otherwise.

TYPICAL FAR FIELD



DRAWING

